DATA SHEET ULTRASTAR SERV24



Ultrastar® Serv24

♦ Features

- Up to 184TB1 in a 2U unit
- Up to 24 NVMe SSDs with a range of capacities and endurance options
- High-performance Intel® "Purley"based server with a choice of CPUs
- 2 512GB SSD boot drives
- 256GB DDR4 DRAM
- 2-port 10GbE included
- 1-port 1GbE for system management
- 2 PCIe x16 slots available for add-in cards
- Enterprise-grade redundant and hotswappable PSUs and fans

The Storage Server Platform for Software-Defined Storage

There is a never-ending need to increase data center performance for storage-intensive applications. To fully realize the benefits of a software-defined storage (SDS) infrastructure, purpose-built storage platforms have become the preferred building blocks for many enterprise data centers.

The Ultrastar Serv24 is designed to be a performance-optimized platform for SDS. By integrating CPUs and NVMe™ SSDs in the same unit, our storage server provides a tested and validated building block for deploying the SDS stack on high-performance storage.

Designed for Fast Data

Flash technology has revolutionized the performance of storage systems; NVMe technology extends flash storage to its full potential. Built upon our storage expertise, the Ultrastar Serv24 features the latest Intel® Xeon® CPUs. Chipset, core count and power can be customized, providing the flexibility to meet varying requirements depending on data workload and performance requirements.

Whether as a stand-alone file server or part of a scaleout deployment, the Ultrastar Serv24 is built to deliver screaming performance in software-defined storage environments. With low latency and consistently high bandwidth, data is accelerated to the speed of flash.



Ultrastar Serv24 - front

Ultrastar Serv24 - back

DATA SHEET ULTRASTAR SERV24



Ultrastar® Serv24

Designed Enterprise and Cloud Data Centers:

The Ultrastar Serv24 is designed to elevate flash performance in demanding, software-defined storage environments.

Specifications

Max. Drives	24 x 2.5" NVMe SSDs
Available SSD Capacities	 3.20TB/1.60TB, 1.2/1.7 DW/D, SanDisk® Skyhawk™ 3.84TB/1.92TB, 0.5/0.6 DW/D, SanDisk Skyhawk 6.4TB 3 DW/D, HGST Ultrastar® SN200 7.68TB 1 DW/D, HGST Ultrastar SN200
Available CPU Choices	Entry-Level: Xeon 5120, 2.2GHz, 14C, 105W Mid-Range: Xeon 6140, 2.3GHz, 18C, 140W High-Perf: Xeon 8160, 2.1GHz, 24C, 150W
Memory	256GB DDR4 Installed (8x 32GB DIMMs)24 DIMM Slots on Motherboard
Expansion	2 PCIe Gen3 x16 and 1 PCIe Gen3 x8 slot
Networking	 1 OCP 2.0 Mezz. Card, Connector A+C, Type 1 1 Dedicated 1GbE RJ45 for IPMI
I/O	2 USB 3.01 VGA, DB151 Serial, DB9
Management	IPMI 2.0 system management
Physical Dimensions	Height: 87mm (3.43") Width: 448mm (17.64") Depth: 760mm (29.92")
Max. Weight	 Product w/o SSDs: ~20.5 kg (45.2 lbs) Product w/ 24 SSDs: ~24.9 kg (54.9 lbs)
Power	 1+1 1200W, CRPS, 80+ Platinum 1+1 1200W, CRPS, 80+ Platinum 200-240V AC input 200-240V AC input
Cooling	5+1 60mm fans, hot-swappable
Serviceability	Hot-swappable power supplies, fans, and SSD modules
Environmental	Operating Temperature: 5 to 35°C Non-op Temperature: -30 to 60°C Humidity: -12°C dew point, 5 to 85% relative humidity Operating Altitude: 40°C @ 3,000ft Sound Power: < 7.5Bels @ 23±2°C

Contact

Sales Inquiries
North America: salesNA@hgst.com
Europe/Middle East/Africa (EMEA): salesEMEA@hgst.com
Asia/Pacific: salesAP@hgst.com
Japan: salesJP@hgst.com

Information & Technical Support http://www.hast.com/support/platforms-support

Partner Program Inquiries channelpartners@hgst.com

Western Digital Corporation 5601 Great Oaks Parkway

San Jose, CA 95119 USA

© 2018 Western Digital Corporation or its affiliates. All rights reserved. Western Digital, SanDisk, the HGST logo, and Ultrastar are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. Skyhawk is used under license from Western Digital Technologies, Inc. Intel and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries. All other marks are the property of their respective owners. References in this publication to HGST-branded products, programs, or services do not imply that they will be made available in all countries. Product specifications provided are sample specifications and do not constitute a warranty. Actual specifications for unique part numbers may vary. Please visit the Support section of our website, http://www.hgst.com/support/platformssupport, for additional information on product specifications. Pictures shown may vary from actual products.